



**HYTORC**<sup>®</sup>  
Since 1968

**Tool Model: HY-10MXT**  
**Pressure/Torque Conversion Chart**

PRESSURE IN: PSI	TORQUE IN:			PRESSURE IN: BAR
	ft-lbs	KGM	NM	
1500	1755	243	2379	104
1600	1864	258	2527	110
1800	2082	288	2822	124
2000	2300	318	3118	138
2200	2526	349	3424	152
2400	2752	381	3731	165
2600	2978	412	4037	179
2800	3204	443	4343	193
3000	3430	474	4650	207
3200	3656	506	4956	220
3400	3882	537	5262	234
3600	4108	568	5569	248
3800	4334	599	5875	262
4000	4560	631	6182	276
4200	4792	663	6496	290
4400	5024	695	6811	303
4600	5256	727	7125	317
4800	5488	759	7440	331
5000	5720	791	7754	345
5200	5948	823	8063	358
5400	6176	854	8372	372
5600	6404	886	8681	386
5800	6632	917	8890	400
6000	6860	949	9299	414
6200	7094	981	9617	427
6400	7328	1013	9934	441
6600	7562	1046	10251	455
6800	7796	1078	10568	468
7000	8030	1111	10885	482
7200	8264	1143	11203	496
7400	8498	1175	11520	510
7600	8732	1208	11837	524
7800	8966	1240	12154	538
8000	9200	1272	12472	552
8200	9432	1304	12786	565
8400	9664	1336	13101	579
8600	9896	1369	13415	593
8800	10128	1401	13730	607
9000	10360	1433	14044	620
9200	10592	1465	14359	634
9400	10824	1497	14673	648
9600	11056	1529	14988	662
9800	11288	1561	15302	676
10000	11520	1593	15617	690

**Hytorc West**

<http://www.hytorcwest.com>

## Important Safety Instructions

**WARNING:** Your **HYTORC TORQUE MACHINE** is a power tool, and as with any power tool, certain safety precautions should be observed to avoid accidents or personal injury. The following tips will assist you.

- **READ ALL INSTRUCTIONS.**
- **KEEP WORK AREA CLEAN AND WELL LIT.**
- **CONSIDER WORK AREA ENVIRONMENT.** Electrical Pumps should never be used in any atmosphere which can be considered potentially volatile. If there is any doubt, use an air pump. Also Note: metal to metal contact can cause sparks, precautions should be taken.
- **AVOID PREMATURE TOOL STARTING.** The Pump Remote Control is for the TOOL OPERATOR only.
- **STAY CLEAR DURING OPERATION.** In most cases, the tool will allow “hands free” operation. If the tool must be held or steadied during operation, use alternative means of securing the tool to the application.
- **GUARD AGAINST ELECTRIC SHOCK.** Ensure the pump is properly grounded and the proper voltage is being used.
- **STORE IDLE TOOLS.** When not in use, tools and accessories should be properly stored to avoid deterioration.
- **USE RIGHT TOOL.** Don't force small tools or attachments to do the job of a larger tool. Don't use tool for purposes not intended.
- **PROPER SAFETY ATTIRE.** When handling/operating hydraulic equipment, use work gloves, hard hats, safety shoes and other applicable clothing.
- **USE SAFETY GLASSES.**
- **Moving equipment.** Do not use hydraulic hoses, uniswivels, pump power or remote cords as means of moving the equipment.
- **MAINTAIN TOOLS WITH CARE.** For top performance, inspect tool, powerpack and accessories for visual damage frequently and always prior to use. Always follow instructions for proper tool and pump maintenance. Refer to the Operations maintenance Section for further clarification.
- **STAY ALERT.** Watch what you are doing. Use common sense. Do not use power equipment under the influence of any mood altering substances.
- **PRIOR TO OPERATION.**  
Ensure that all hydraulic connections are securely connected and there is no leakage.  
Verify that the hydraulic hoses are not kinked or otherwise damaged.  
Insure the square drive and its retainer is fully and securely engaged.  
Ascertain that all connectors, elbows, fittings and swivels are not bent, loose or damaged.
- **PRIOR TO USE.**  
Check Sockets for size, quality and flaws. (Do not use if question able.)  
Cycle tool to ensure proper function.  
Locate a solid, secure reaction point.  
Be sure the reaction arm retaining clamp is fully engaged.  
Be sure the hydraulic hoses are free of the reaction point.  
Pressurize the system momentarily if the tool tends to “ride up” or to “creep”, stop and re-adjust the reaction arm to a more solid and secure position.  
  
NOTE: Remain clear of the reaction arm during operation and never put body parts between reaction arm and reaction surface.
- **ALWAYS USE QUALITY ACCESSORIES.** Always use top quality impact sockets in good condition which are the correct size and fully engage the nut. Hidden flaws, however, remain a possibility which could cause break, so stay clear of sockets during operation.
- **DO NOT USE** other equipment to enhance performance. (Hammer on Socket/Tool)
- **NOTE:** HYTORC Pumps are designed to operate HYTORC Tools only. Damage may occur to the pump or product that is being operated due to misuse.

**SAVE THESE INSTURCTIONS FOR FUTURE USE!**