



BOLTING TECHNOLOGY
 tel: +33 556 775 000
 fax: +33 556 775 052
 email: info@hytorcbt.com

Middle East & North Africa

TOOL MODEL: VERSA 1

Pressure in PSI	Torque in			Pressure in BAR
	FT.LBS	KG.M	N.M	
1 500	115	16	156	104
1 600	122	17	166	110
1 800	138	19	187	124
2 000	153	21	207	138
2 200	168	23	228	152
2 400	184	25	249	165
2 600	199	28	270	179
2 800	215	30	291	193
3 000	230	32	312	207
3 200	246	34	333	220
3 400	262	36	355	234
3 600	277	38	376	248
3 800	293	40	397	262
4 000	309	43	419	276
4 200	325	45	441	290
4 400	341	47	462	303
4 600	357	49	484	317
4 800	373	52	506	331
5 000	389	54	527	345
5 200	405	56	549	358
5 400	421	58	571	372
5 600	437	60	592	386
5 800	453	63	614	400
6 000	469	65	636	414
6 200	485	67	658	427
6 400	502	69	680	441
6 600	518	72	702	455
6 800	534	74	724	468
7 000	550	76	746	482
7 200	566	78	767	496
7 400	581	80	788	510
7 600	598	83	810	524
7 800	613	85	831	538
8 000	629	87	853	552
8 200	645	89	875	565
8 400	662	91	897	579
8 600	678	94	919	593
8 800	694	96	941	607
9 000	710	98	962	620
9 200	726	100	984	634
9 400	741	102	1 005	648
9 600	758	105	1 027	662
9 800	773	107	1 048	676
10 000	789	109	1 070	690